



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture LPS® Revo 66
Registration number -
Synonyms None.
Part Number 04416, M04416
Issue date 19-April-2014
Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses An aerosol remover of dirt, moisture, dust, flux or oxides from the internal components of electronic or precision equipment.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier Geocel Limited
Company name Western Wood Way, Langage Science Park, Plympton,
Address Plymouth, PL7 5BG
United Kingdom
Telephone +44 (0)1752 202060 / +44 (0)1752 334384
In Case of Emergency +001 703-527-3887
Manufacturer
Company name LPS Laboratories, a division of Illinois Tool Works, Inc.
Address 4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)
Website <http://www.lpslabs.com>
e-mail sds@lpslabs.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification R5, Xn;R20, R52/53

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols Category 3 H229 - Pressurized container: May burst if heated.

Health hazards

Acute toxicity, inhalation Category 4 H332 - Harmful if inhaled.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard Category 3 H412 - Harmful to aquatic life with long lasting effects.

Hazard summary

Physical hazards Heating may cause an explosion.
Health hazards Harmful by inhalation.
Environmental hazards Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Specific hazards Harmful by inhalation. Do not breathe dust/fume/gas/mist/vapors/spray. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Main symptoms Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended**Contains:** 1,2-TRANS-DICHLOROETHYLENE, Isopropanol**Hazard pictograms****Signal word** Warning**Hazard statements**

H229 Pressurized container: May burst if heated.
 H332 Harmful if inhaled.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements**Prevention**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P251 Pressurised container: Do not pierce or burn, even after use.
 P261 Avoid breathing gas.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.

Response

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information 40,97 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.**2.3. Other hazards** None known.**SECTION 3: Composition/information on ingredients****3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
1,2-TRANS-DICHLOROETHYLENE	50 - 60	156-60-5 205-860-2	-	602-026-00-3	
Classification:	DSD: F;R11, Xn;R20, R52/53				C
	CLP: Flam. Liq. 2;H225, Acute Tox. 4;H302, Acute Tox. 4;H332, Aquatic Chronic 3;H412				C
Isopropanol	3 - 5	67-63-0 200-661-7	-	603-117-00-0	
Classification:	DSD: F;R11, Xi;R36, R67				
	CLP: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336				

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Composition comments The full text for all R- and H-phrases is displayed in section 16.**SECTION 4: First aid measures****General information**

In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTRE or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control centre immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Direct contact with eyes may cause temporary irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media Water. Water spray. Foam. Carbon dioxide (CO₂). Dry powder.

Unsuitable extinguishing media None known.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Fully encapsulating, vapour protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent product from entering drains. Following product recovery, flush area with water.

6.4. Reference to other sections

Use personal protection recommended in Section 8 of the SDS. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Observe good industrial hygiene practices. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits****Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001**

Components	Type	Value
1,2-TRANS-DICHLOROETHYLENE (CAS 156-60-5)	MAK	790 mg/m ³
	STEL	200 ppm
		3160 mg/m ³
Isopropanol (CAS 67-63-0)	MAK	800 ppm 500 mg/m ³
	STEL	200 ppm
		2000 mg/m ³ 800 ppm

Belgium. Exposure Limit Values.

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1000 mg/m ³
		400 ppm
	TWA	500 mg/m ³ 200 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m ³
	TWA	980 mg/m ³

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Isopropanol (CAS 67-63-0)	MAC	999 mg/m ³
		400 ppm
	STEL	1250 mg/m ³ 500 ppm

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value
Isopropanol (CAS 67-63-0)	TWA	980 mg/m ³
		400 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
Isopropanol (CAS 67-63-0)	Ceiling	1000 mg/m ³
	TWA	500 mg/m ³

Denmark. Exposure Limit Values

Components	Type	Value
1,2-TRANS-DICHLOROETHYLENE (CAS 156-60-5)	TLV	790 mg/m ³
		200 ppm
Isopropanol (CAS 67-63-0)	TLV	490 mg/m ³
		200 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	600 mg/m ³
		250 ppm
	TWA	350 mg/m ³ 150 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
1,2-TRANS-DICHLOROET HYLENE (CAS 156-60-5)	STEL	1000 mg/m3
	TWA	250 ppm 800 mg/m3
Isopropanol (CAS 67-63-0)	STEL	200 ppm 620 mg/m3
	TWA	250 ppm 500 mg/m3 200 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Isopropanol (CAS 67-63-0)	VLE	980 mg/m3 400 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
1,2-TRANS-DICHLOROET HYLENE (CAS 156-60-5)	TWA	800 mg/m3
		200 ppm
Isopropanol (CAS 67-63-0)	TWA	500 mg/m3 200 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
Isopropanol (CAS 67-63-0)	AGW	500 mg/m3 200 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
	TWA	500 ppm 980 mg/m3 400 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	2000 mg/m3
	TWA	500 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
1,2-TRANS-DICHLOROET HYLENE (CAS 156-60-5)	TWA	790 mg/m3
		200 ppm
Isopropanol (CAS 67-63-0)	TWA	490 mg/m3 200 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Italy. Occupational Exposure Limits

Components	Type	Value
1,2-TRANS-DICHLOROET HYLENE (CAS 156-60-5)	TWA	200 ppm
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
	TWA	350 mg/m3

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
Isopropanol (CAS 67-63-0)	TLV	245 mg/m3 100 ppm

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Type	Value
1,2-TRANS-DICHLOROET HYLENE (CAS 156-60-5)	TWA	700 mg/m3
Isopropanol (CAS 67-63-0)	STEL	1200 mg/m3
	TWA	900 mg/m3

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
1,2-TRANS-DICHLOROET HYLENE (CAS 156-60-5)	TWA	200 ppm
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	500 mg/m3
		203 ppm
	TWA	200 mg/m3
		81 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Isopropanol (CAS 67-63-0)	TWA	500 mg/m3
		200 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm

Sweden. Occupational Exposure Limit Values

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
1,2-TRANS-DICHLOROET HYLENE (CAS 156-60-5)	STEL	1580 mg/m3
		400 ppm
	TWA	790 mg/m3

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	200 ppm
		1000 mg/m3
	TWA	400 ppm
		500 mg/m3
		200 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1250 mg/m3
		500 ppm
	TWA	999 mg/m3
		400 ppm

Biological limit values**Germany. TRGS 903, BAT List (Biological Limit Values)**

Components	Value	Determinant	Specimen	Sampling time
Isopropanol (CAS 67-63-0)	25 mg/l	Aceton	Urine	*
	25 mg/l	Aceton	Blood	*

* - For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4

Components	Value	Determinant	Specimen	Sampling time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetona	Urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling time
Isopropanol (CAS 67-63-0)	25 mg/l	Aceton	Urine	*
	25 mg/l	Aceton	Blood	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no-effect level (DNEL) Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection For prolonged or repeated skin contact use suitable protective gloves. Chemical resistant gloves are recommended.

- Other Not available.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Not applicable.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Contain spills and prevent releases and observe national regulations on emissions. Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	Liquid.
Physical state	Gas.
Form	Aerosol
Colour	Clear colorless or nearly colorless
Odour	Mild.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	42 °C (107,6 °F)
Flash point	Not applicable
Evaporation rate	< 1 BuAc
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	868 mm Hg @20 °C
Vapour density	> 1
Relative density	Not available.
Solubility(ies)	
Solubility (water)	< 5 %
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	460 °C (860 °F) estimated
Decomposition temperature	Not available.
Viscosity	< 3 cSt @25 °C
Explosive properties	Not available.
Oxidizing properties	Not available.
9.2. Other information	
Percent volatile	100 %
Specific gravity	1,2 - 1,3 @20 °C
VOC (Weight %)	64,7 % per US State and Federal Consumer Product Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity	Strong oxidising agents.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	Hazardous polymerisation does not occur.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
10.5. Incompatible materials	Strong oxidising agents. Reacts violently with sodium, potassium, barium metal. Reacts with finely divided aluminum, zinc and magnesium.
10.6. Hazardous decomposition products	Combustion will generate smoke, possibly thick and choking, resulting in zero visibility and combustion products include hydrogen fluoride, hydrogen chloride, fluorine, chlorine, carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
Information on likely routes of exposure	
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Inhalation	Harmful by inhalation.
Skin contact	Based on available data, the classification criteria are not met.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms Direct contact with eyes may cause temporary irritation. Exposed may experience eye tearing, redness, and discomfort. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.1. Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components	Species	Test results
1,2-TRANS-DICHLOROETHYLENE (CAS 156-60-5)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	21723 mg/l, 6 Hours
<i>Oral</i>		
LD50	Rat	1235 mg/kg
<i>Other</i>		
LD50	Mouse	4019 mg/kg
	Rat	7411 mg/kg
Isopropanol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12800 mg/kg 16,4 ml/kg
<i>Inhalation</i>		
LC50	Rat	> 10000 ppm
<i>Oral</i>		
LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg
	Rabbit	5,03 g/kg
	Rat	4,7 g/kg
<i>Other</i>		
LD50	Mouse	1509 mg/kg
	Rat	1099 mg/kg

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

ACGIH Carcinogens

Isopropanol (CAS 67-63-0) Not classifiable as a human carcinogen. A4

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Mixture versus substance information No information available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test results
Isopropanol (CAS 67-63-0)		
Aquatic		
Fish	LC50 Bluegill (<i>Lepomis macrochirus</i>)	> 1400 mg/l, 96 hours
12.2. Persistence and degradability	No data is available on the degradability of this product.	
12.3. Bioaccumulative potential	No data available.	
Partition coefficient n-octanol/water (log Kow)		
1,2-TRANS-DICHLOROETHYLENE		2,06
Isopropanol		0,05
Bioconcentration factor (BCF)	Not available.	
12.4. Mobility in soil	No data available.	
12.5. Results of PBT and vPvB assessment	Not available.	
12.6. Other adverse effects	Not assigned.	

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, asphyxiant
14.3. Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Hazard No. (ADR)	Not available.
Tunnel restriction code	3 (E)
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

RID

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, asphyxiant
14.3. Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

ADN

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, asphyxiant
14.3. Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

IATA

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, non-flammable
14.3. Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, non-flammable
14.3. Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
14.4. Packing group	Not applicable.
14.5. Environmental hazards	
Marine pollutant	No
EmS	F-D, S-U
14.6. Special precautions for user	Not available.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not listed.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Not listed.

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not listed.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

1,2-TRANS-DICHLOROETHYLENE (CAS 156-60-5)

Isopropanol (CAS 67-63-0)

Directive 94/33/EC on the protection of young people at work

Not listed.

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations

Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R11 Highly flammable.

R20 Harmful by inhalation.

R36 Irritating to eyes.

R5 Heating may cause an explosion.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

Revision information

H412 Harmful to aquatic life with long lasting effects.
Product and Company Identification: Product Uses
Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
Regulatory Information: United States
GHS: Classification

Training information

Follow training instructions when handling this material.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.