

Performance you can trust

TRI-Logic® HO32 Hydraulic Oil for Machine Tools

TRI-Logic® HO32 is a premium quality oil specifically designed for use in the hydraulic systems of machine tools. TRI-Logic® HO32 is designed to resist the tendency to generate deposits, sludge and varnish so giving increased service life and extended oil change intervals.

The unique formulation of TRI-Logic® HO32 (World patent rights pending) minimises the detrimental effects on cutting fluid emulsions usually associated with hydraulic oil leaks. Rather than acting as a food source for bacteria and fungi, therefore promoting growth, TRI-Logic® HO32 resists degradation.

The TRI-Logic® system is a revolutionary approach to maximising cutting fluid sump life, minimising fluid disposal and reducing costs. For optimum performance TRI-Logic® HO32 hydraulic oil should be used as part of the TRI-Logic® system.

Features

- Excellent anti-wear properties.
- Good filterability.
- High thermal stability.
- Excellent corrosion protection.
- Low foaming.
- Resists degradation.
- Optimised for use in the TRI-Logic® system.

Directions for Use

TRI-Logic® HO32 is designed for use in any machine tool where an ISO VG32 lubricant is designated. Ideally lubrication systems should be drained before filling with TRI-Logic® HO32 in accordance with the machine tool manufacturers recommendations.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Technical Data

ROCOL[®]

Performance you can trust

TRI-Logic[®] HO32

Appearance	Clear amber liquid
Odour	Mild
Viscosity at 40°C	ISO VG32
Density at 20°C	0.84 g/cm ³
Storage	Store at normal ambient temperature (5 to 30°C)
Pack Sizes – Part Codes	200 ltr - 51949 1000 ltr - 51945

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.