

ANTI-SEIZE SPRAY

Page: 1

Compilation date: 09/11/2015

Revision date: 04/02/2016

Revision No: 11

## Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ANTI-SEIZE SPRAY

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Anti-seize agent.

### **1.3. Details of the supplier of the safety data sheet**

#### Company name: ROCOL

	ROCOL House				
	Swillington				
	Leeds				
	West Yorkshire				
	LS26 8BS				
	ENGLAND				
Tel:	+44 (0) 113 232 2700				
Fax:	+44 (0) 113 232 2740				

Email: <u>customer-service@rocol.com</u>

### 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

# Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP:	Skin Irrit. 2: H315; STOT SE 3: H336; Flam. Aerosol 1: H222; Aquatic Chronic 3: H412; -:
	H229; Aquatic Chronic 2: H411
Most important adverse effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin
	irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting
	effects.

#### 2.2. Label elements

Label elements:		
Hazard statements:	H222: Extremely flammable aerosol.	
	H229: Pressurised container: May burst if heated	
	H315: Causes skin irritation.	
	H336: May cause drowsiness or dizziness.	
	H411: Toxic to aquatic life with long lasting effects.	
Hazard pictograms:	GHS02: Flame	
	GHS07: Exclamation mark	[cont]

ANTI-SEIZE SPRAY

**Page:** 2



 Signal words:
 Danger

 Precautionary statements:
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

 P211: Do not spray on an open flame or other ignition source.
 P251: Do not pierce or burn, even after use.

 P280: Wear protective gloves/protective clothing/eye protection/face protection.

 P302+352: IF ON SKIN: Wash with plenty of water/.

 P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Hazardous ingredients:

### HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) - REACH registered number(s): EXEMPT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
270-704-2	68476-85-7	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	50-70%

### HEPTANE & ISOMERS - REACH registered number(s): 01-2119475515-33-XXXX

295-434-	2 92045-53-9	-	Flam. Liq. 2: H225; Aquatic Chronic 2:	10-30%
			H411; Skin Irrit. 2: H315; STOT SE 3:	
			H336; Asp. Tox. 1: H304	

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (NOTE L - < 3% DMSO EXTRACT)

265-097-6	64741-96-4	Substance with a Community	-	1-10%
		workplace exposure limit.		

#### COPPER POWDER

231-159-6	7440-50-8	-	Acute Tox. 4: H302; Aquatic Acute 1:	1-10%
			H400; Aquatic Chronic 2: H411	

### **GRAPHITE POWDER**

231-955-3	7782-42-5	Substance with a Community	-	1-10%
		workplace exposure limit.		

# ANTI-SEIZE SPRAY

# **Page:** 3

ACETONE - REACH registered number(s): 01-2119471330-49-XXXX

ACETONE - R	EACH register	red number(s): 01-2119471330-49-X	KXX		
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%	
CALCIUM CAF	RBONATE				
2151-79-6	1317-65-3	Substance with a Community workplace exposure limit.	-	1-10%	
ection 4: First a	aid measures	S			
4.1. Description	of first aid m	easures			
S	Skin contact:	Wash immediately with plenty of soa	ap and water. Consult a doctor.		
	Eye contact:	Bathe the eye with running water for	15 minutes. Consult a doctor.		
	Ingestion:	Wash out mouth with water. Do not	induce vomiting. Consult a doctor.		
	Inhalation:	Remove casualty from exposure en	suring one's own safety whilst doing so. Cons	ult a	
		doctor.			
4.2. Most import	tant symptom	is and effects, both acute and delay	yed		
g	Skin contact:	There may be irritation and redness	at the site of contact.		
		There may be irritation and redness			
		<b>n:</b> There may be soreness and redness of the mouth and throat. May cause dizziness.			
		-	with a feeling of tightness in the chest. Drows		
		or mental confusion may occur.			
Delayed / immed	diate effects:	No data available.			
4.3. Indication o	of any immedi	ate medical attention and special t	reatment needed		
nmediate / speci	al treatment:	No data available.			
ection 5: Fire-fi	ghting meas	sures			
5.1. Extinguishi	ng media				
Extinguis	shing media:	Do not use water. Alcohol resistant	foam. Carbon dioxide. Dry chemical powder.	Use	
-	-	water spray to cool containers.			
5.2. Special haz	ards arising f	rom the substance or mixture			
Expos	<b>Exposure hazards:</b> Extremely flammable. Forms explosive air-vapour mixture. In combustion emits toxic			DXIC	
5.3. Advice for f	iro-fightors	fumes of carbon dioxide / carbon mo	DIOXIDE.		
Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact			ntact		
with skin and eyes.					

### ANTI-SEIZE SPRAY

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

6.2. Environmental precautions

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

### Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden.

#### 7.2. Conditions for safe storage, including any incompatibilities

ignition.

6.3. Methods and material for containment and cleaning up

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight. Ensure lighting and electrical equipment are not a source of ignition. . ICC INTERNATIONAL FIRE CODE 2006 AEROSOL CLASSIFICATION LEVEL 3

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

### HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)

#### Workplace exposure limits:

#### **Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000ppm 1750mg/m3	1250ppm 2180mg/m3	-	-

## **HEPTANE & ISOMERS**

UK 500 ppm, 2085	ma/m3 -	-	-
------------------	---------	---	---

# ANTI-SEIZE SPRAY

UK         5 mg/m3         10 mg/m3         -         -           COPPER POWDER         UK         1 mg/m3         2 mg/m3         -         -           GRAPHITE POWDER         UK         -         -         5 mg/m3         10 mg/m3           GRAPHITE POWDER         UK         -         -         5 mg/m3         10 mg/m3           UK         1210 mg/m3         3620 mg/m3         -         -         -           UK         1210 mg/m3         3620 mg/m3         -         -           UK         1210 mg/m3         3620 mg/m3         -         -           UK         1210 mg/m3         3620 mg/m3         -         -           DIK         Mag/m3         -         -         -	DISTILLATE	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (NOTE L - < 3% DMSO EXTRACT)						
UK         1mg/m³         2mg/m³         -         -           GRAPHITE POWDER	UK	5 mg/m3	10 mg/m3	-	-			
GRAPHITE POWDER           UK         -         -         5 mg/m³         10 mg/m³           ACETONE         UK         1210 mg/m³         3620 mg/m³         -         -           UK         1210 mg/m³         3620 mg/m³         -         -         -	COPPER PC	OWDER						
UK         -         5 mg/m³         10 mg/m3           ACETONE         UK         1210 mg/m³         3620 mg/m³         -         -           UK         1210 mg/m³         3620 mg/m³         -         -         -	UK	1mg/m <sup>3</sup>	2mg/m3	-	-			
ACETONE         UK         1210 mg/m3         3620 mg/m3         -         -           CALCIUM CARBONATE         UK         -         -         4 mg/m3         -	<b>GRAPHITE</b>	POWDER						
UK         1210 mg/m3         3620 mg/m3         -         -           CALCIUM CARBONATE         UK         -         4 mg/m3         -	UK	-	-	5 mg/m³	10 mg/m3			
CALCIUM CARBONATE           UK         -         -         4 mg/m3         -	ACETONE							
UK 4 mg/m3 -	UK	1210 mg/m3	3620 mg/m3	-	-			
	CALCIUM C	ARBONATE						
	UK	-	-	4 mg/m3	-			
	DNEL/PNEC V	DNEL/PNEC Values						

#### Hazardous ingredients:

#### ACETONE

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	186	Workers	Local
DNEL	Inhalation	2420	Workers	Local
DNEL	Oral	62	Consumers	Systemic
PNEC	Fresh water	10.6	-	-
PNEC	Marine water	1.06	-	-
PNEC	Soil (agricultural)	33.3	-	-
PNEC	-	-	-	-

#### 8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical		
	equipment are not a source of ignition.		
Respiratory protection:	Respiratory protection not normally required for normal use in well ventilated areas.		
	Respiratory protection should be used in enclosed spaces, with poor ventilation, for		
	extended repeated use, or where exposure limits may be exceeded. Recommended		
	filter types are A1P2 or A2P2. Gas/vapour filter, type A: organic vapours (EN141).		
Hand protection:	Nitrile gloves.		
Eye protection:	Safety glasses with side-shields.		
Skin protection:	Protective clothing.		
Environmental:	No data available		

# Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Aerosol

## ANTI-SEIZE SPRAY

Colour:	Dark brown	
Odour:	Characteristic odour	
Evaporation rate:	Fast	
Oxidising:	Non-oxidising (by EC criteria)	
Solubility in water:	Not miscible	
Viscosity:	Non-viscous	
Boiling point/range°C:	<0 Melting point/range°C:	<-130
Flammability limits %: lower:	1.8 upper:	9.4
Flash point°C:	<-100 Autoflammability°C:	430
Relative density:	<1	
9.2 Other information		

9.2. Other information

Other information: No data available.

### Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No data available.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

# 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

#### Section 11: Toxicological information

11.1. Information on toxicological effects

#### Hazardous ingredients:

#### **HEPTANE & ISOMERS**

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	HMN	4H LC50	>20	mg/l

**Page:** 6

# ANTI-SEIZE SPRAY

### Page: 7

### ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3	gm/kg
ORL	RAT	LD50	5800	mg/kg

# CALCIUM CARBONATE

ORAL	RAT	LD50	>2000	mg/kg

### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: No data available.

Other information: Not applicable.

# Section 12: Ecological information

12.1. Toxicity

### Hazardous ingredients:

#### **HEPTANE & ISOMERS**

ALGAE	96H ErC50	> 10 - < 100	mg/l
DAPHNIA	96H ErC50	>1 - < 10	mg/l
Daphnia magna	96H ErC50	> 10 - < 10	-
FISH	96H LC50	>1 - < 10	mg/l

#### ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l
--------------------------------	------	------	------

### CALCIUM CARBONATE

ALGAE	72H ErC50	>100	mg/l
DAPHNIA	48H EC50	>100	mg/l

# ANTI-SEIZE SPRAY

	ANT	-SEIZE SPRAT			
				Pa	a <b>ge:</b> 8
FISH		96H LC50	>100	g/l	
12.2. Persistence and degrad	lability				
ersistence and degradability:	-	le			]
12.3. Bioaccumulative potent					
Bioaccumulative potential:	No bioaccumulation poter	ntial.			
12.4. Mobility in soil					
Mobility:	Highly volatile. Heavier th	an air.			
12.5. Results of PBT and vPv	'B assessment				
PBT identification:	This product is not identif	ied as a PBT/vPvB sul	ostance.		
12.6. Other adverse effects					
Other adverse effects:	Harmful to aquatic organi	sms.			
ection 13: Disposal conside	erations				
13.1. Waste treatment metho	ds				
Disposal operations:	No data available.				
Recovery operations:	No data available				
Waste code number:	16 05 04				
Disposal of packaging:	Dispose of in a regulated	landfill site or other m	ethod for hazardous	or toxic wastes.	
NB:	The user's attention is drawn to the possible existence of regional or national				
	regulations regarding disp	oosal.			
ection 14: Transport inform	nation				
14.1. UN number					
UN number:	UN1950				
14.2. UN proper shipping nar	ne				
Shipping name:	AEROSOLS, FLAMMABL	E			
14.3. Transport hazard class	(es)				
Transport class:	2.1				
14.4. Packing group					

Packing group: n/a

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No data available

## ANTI-SEIZE SPRAY

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

#### Transport in bulk: No data available.

# Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: ICC INTERNATIONAL FIRE CODE 2006 AEROSOL CLASSIFICATION LEVEL 3

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

### Section 16: Other information

#### Other information

Other information:	EC Directive 94/1/EC adapting some technicalities of Council Directive 75/324/EEC on
	the approximation of the laws of Member States relating to aerosol dispensers.
	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	Compiled in accordance with REACH.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H220: Extremely flammable gas.
	H222: Extremely flammable aerosol.
	H225: Highly flammable liquid and vapour.
	H229: Pressurised container: May burst if heated
	H280: Contains gas under pressure; may explode if heated.
	H302: Harmful if swallowed.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	H400: Very toxic to aquatic life.
	H411: Toxic to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.