

Accu-Lube® LS-10 Paste

Hand-Applied Lubricants

FEATURES

- Solid paste lubricant
- Reduces friction for cleaner cutting and better finish
- Vegetable-based lubricant
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

APPLICATIONS

- Short-run machining
- Burring
- Tapping
- Drilling

DIRECTIONS

For application on any cutting tool. Apply with brush or immerse tool in paste.

HANDLING

Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

STORAGE

Keep container tightly closed in a dry and well-ventilated place

DISPOSAL INFORMATION

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

Appearance/physical state	Solid
Odor	Mild
Melting point/freezing point	110-120°F/43-49°C
Boiling point/range	>400°F/>204°C
Vapor pressure	<1 mmHg
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	10.07
Color	Blue
Flash point	>200°F/>93°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	>1
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	0.86
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
07603	8 fl. oz.	jar	16	10 lbs.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved



Официальный дистрибьютор в России ООО "РаделМаркет"

195030, г. Санкт-Петербург, ул. Химиков, д. 28АС

тел. +7(800) 333-28-23, +7(812) 448-13-41, +7(495) 725-43-72, +7(343) 237-24-98

ИНН 7813363596 КПП 780601001 ОГРН 1069847532864 Сайт <https://radelmarket.ru> Э/п zakaz@radelmarket.ru