

MTS1000 Grease (AFS 1152)

High load molybdenum disulphide plain bearing grease

Product Overview

ROCOL® MTS1000 Grease (AFS 1152) is a heavy duty bearing grease fortified with molybdenum disulphide. It has been designed for the effective lubrication and protection of plain bearings and sliding surfaces used in extreme environments, particularly in heavily loaded, slow moving applications.

MTS1000 Grease (AFS 1152) combines the resilience of a clay thickener with the addition of molybdenum disulphide ensuring that a lubricating film exists under the most extreme loadings where the grease film can be squeezed out.

Features and Benefits

- MTS1000 Grease (AFS 1152) has a good temperature resistance from -20°C to +150°C.
- It is a non-melting grease, fortified with molybdenum disulphide, for excellent temperature and water resistance.
- Molybdenum disulphide (MoS₂) has an affinity to the metal surfaces leaving a tenacious high load carrying film with a low coefficient of friction. This film provides an extremely durable layer reducing frictional heat and wear and extending component life and lubrication intervals.
- Ideal for highly loaded, applications where shock loads and vibration can occur.
- MTS1000 Grease (AFS 1152) offers excellent corrosion resistance to protect in humid, damp and even wet conditions.
- MTS1000 Grease (AFS 1152) maintains its integrity in arduous conditions and continues to protect over extended lubrication intervals, reducing equipment failure, downtime and lubricant usage.

Directions for Storage and Use

- MTS1000 Grease (AFS 1152) can be applied manually, by grease gun, keg pump or by other methods suitable for dispensing NLGI No. 2 greases with solid additives.
- MTS1000 Grease (AFS 1152) is compatible with other clay thickened greases. However, for best results the previous lubricant should be removed prior to application.
- Avoid mixing MTS1000 Grease (AFS 1152) with soap thickened greases.
- The storage temperature should be controlled between +1°C and +40°C.
- Shelf life is 3 years from date of manufacture.

Specifications

- AFS 1152A

Typical Applications

MTS1000 Grease (AFS 1152) is particularly suitable for heavily loaded, slow moving applications typically found in industries such as quarries, mining, marine, aerospace, MoD, docks, agriculture and construction.

MTS1000 Grease (AFS 1152) excels in applications such as crushers, screens, presses, loaders, scrapers, wagons and similar applications where plain bearings, pins, bushes, slides etc. are subjected to extreme conditions.

Pack Sizes

Pack Size	Part Code
500g	16143

MTS1000 Grease (AFS 1152)

High load molybdenum disulphide plain bearing grease

Property	Test Method	Result
Appearance	Visual	Smooth blue / black grease
NLGI No.	IP 50 – ASTM D217	2
Base Type	N/A	Severely refined mineral oil
Base Fluid Viscosity at 40°C	IP 71	184cSt
Base Fluid Viscosity at 100°C	IP 71	15cSt
Thickener	N/A	Organically modified clay
Solids	N/A	Molybdenum disulphide
Temperature Range	N/A	-20°C to + 150°C
4-Ball:		
Weld Load	IP 239 – ASTM D2596	355kg
Mean Hertz Load	IP 239 – ASTM D2596	68kg
Oil Separation 24 hrs at +100°C	IP 121	3% maximum
Water Washout Test	IP 215 – ASTM D1264	0%
Corrosion Test:		
IP 112 – ASTM D130		
24 hrs at +100°C Copper	N/A	1a
Corrosion Test 24 hrs at 100°C:		
Mild Steel	N/A	No stain
Aluminium	N/A	No stain

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 1 Date: 01-11

T +44 (0) 113 232 2600
 F +44 (0) 113 232 2740
 E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001
 Certificate No. FM 12448



BS EN ISO 14001
 Certificate No. EMS 67596



OHSAS 18001
 Certificate No. OHS 78173



INVESTORS
 IN PEOPLE