according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

Wynn's,

MSDS Version: E01.00

Safety Data Sheet

Date of issue: 13/08/2015

Blend Version: 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Product code : Catalytic Converter & Oxygen Sensor Cleaner

: W25692

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture

: Petrol additive.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wynn's Belgium Industriepark-West 46 9100 Sint-Niklaas - Belgium T +32 3 766 60 20 - F +32 3 778 16 56 msds@wynns.eu - www.wynns.be

1.4. Emergency telephone number

Emergency number

: BIG: +32(0)14/58.45.45

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
Org. Perox. E	H242
Acute Tox. 4 (Dermal)	H312
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Muta. 2	H341
STOT RE 1	H372
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Full text of classification categories and H statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Muta.Cat.3; R68 O; R7 Xn; R20/21 Xn; R65 Xn; R48/20 Xi; R36/38 R10 Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

Hazardous ingredients	: 2-butoxyethanol, xylene, Di-tert-butyl peroxide, 2-ethylhexan-1-ol, hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
Hazard statements (CLP)	 H226 - Flammable liquid and vapour H242 - Heating may cause a fire H304 - May be fatal if swallowed and enters airways H312+H332 - Harmful in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H341 - Suspected of causing genetic defects H372 - Causes damage to organs (central nervous system) through prolonged or repeated exposure H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (CLP)	 P102 - Keep out of reach of children P405 - Store locked up P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P260 - Do not breathe vapours P280 - Wear face protection, protective gloves, protective clothing P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor P331 - Do NOT induce vomiting P337+P313 - If eye irritation persists: Get medical advice/attention

2.3. **Other hazards**

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture			
Name	Product identifier	% w	Classification according to Directive 67/548/EEC
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC no) 919-164-8 (REACH-no) 01-2119473977-17	50 - 75	Xn; R48/20 Xn; R65 R66
2-butoxyethanol	(CAS No) 111-76-2 (EC no) 203-905-0 (EC index no) 603-014-00-0 (REACH-no) 01-2119475108-36	10 - 25	Xn; R20/21/22 Xi; R36/38
2-ethylhexan-1-ol	(CAS No) 104-76-7 (EC no) 203-234-3 (REACH-no) 01-2119487289-20	10 - 25	Xn; R20 Xi; R36/37/38
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	10 - 25	R10 Xn; R20/21 Xi; R38
polyetheramine	(CAS No) 224622-34-8	5 - 10	Xi; R38 R52/53
Di-tert-butyl peroxide	(CAS No) 110-05-4 (EC no) 203-733-6 (EC index no) 617-001-00-2 (REACH-no) 01-2119513335-48	2,5 - 5	O; R7 F; R11 Muta.Cat.3; R68 R52/53
Kerosine (petroleum), hydrodesulfurized	(CAS No) 64742-81-0 (EC no) 265-184-9 (EC index no) 649-423-00-8 (REACH-no) 01-2119462828-25	0,1 - 1	Xn; R65 Xi; R38 N; R51/53
Name	Product identifier	Specific concentration limits	
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	(C >= 12,5) Xn;R20/21	
Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC no) 919-164-8 (REACH-no) 01-2119473977-17	50 - 75	STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

Name	Product identifier	% w	Classification according
			to Regulation (EC) No. 1272/2008 [CLP]
2-butoxyethanol	(CAS No) 111-76-2 (EC no) 203-905-0 (EC index no) 603-014-00-0 (REACH-no) 01-2119475108-36	10 - 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
2-ethylhexan-1-ol	(CAS No) 104-76-7 (EC no) 203-234-3 (REACH-no) 01-2119487289-20	10 - 25	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	10 - 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
polyetheramine	(CAS No) 224622-34-8	5 - 10	Skin Irrit. 2, H315 Aquatic Chronic 3, H412
Di-tert-butyl peroxide	(CAS No) 110-05-4 (EC no) 203-733-6 (EC index no) 617-001-00-2 (REACH-no) 01-2119513335-48	2,5 - 5	Flam. Liq. 2, H225 Org. Perox. E, H242 Muta. 2, H341 Aquatic Chronic 3, H412
Kerosine (petroleum), hydrodesulfurized	(CAS No) 64742-81-0 (EC no) 265-184-9 (EC index no) 649-423-00-8 (REACH-no) 01-2119462828-25	0,1 - 1	Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

Description of first aid measures 4.1.

First-aid measures general	: Check the vital functions. Victim conscious with laboured breathing: half-seated. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Vomiting: prevent asphyxia/aspiration pneumonia. Victim in shock: on his back with legs slightly raised. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain.
	Depending on the victim's condition: doctor/hospital.
First-aid measures after inhalation	 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. Ingestion of large quantities: immediately to hospital.
4.2. Most important symptom	s and effects, both acute and delayed
Symptoms/injuries	: Suspected of causing genetic defects.
Symptoms/injuries after inhalation	: Harmful if inhaled.
Symptoms/injuries after skin contact	 Harmful in contact with skin. Causes skin irritation. Repeated or prolonged skin contact may cause dermatitis and defatting.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Harmful if swallowed. Headache. Abdominal pain. Risk of aspiration pneumonia. May be fatal if swallowed and enters airways

Indication of any immediate medical attention and special treatment needed 4.3.

No additional information available

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Sizi Extinguisting inculu	
Suitable extinguishing media	: Water spray. AFFF foam. ABC-powder.
Unsuitable extinguishing media	: Do not use a heavy water stream.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

5.2. Special hazards arising from the substance or mixture		
Fire hazard	: Flammable liquid and vapour. This material can accumulate static charge by flow or agitation and can be ignited by static discharge.	
Explosion hazard	: Product is not explosive.	
5.3. Advice for firefighters		
Firefighting instructions	: Contain the extinguishing fluids by bunding. Prevent fire-fighting water from entering environment.	
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.	
SECTION 6: Accidental release measures		

6.1. Pe	1. Personal precautions, protective equipment and emergency procedures			
General me	easures	: Use special care to avoid static electric charges. No open flames. No smoking.		
6.1.1. Fo	or non-emergency personnel			
Protective e	equipment	: Wear suitable gloves and eye/face protection. protective clothing.		
Emergency	procedures	: Mark the danger area. Seal off low-lying areas. Large spills/in enclosed spaces: compressed air apparatus. Take off contaminated clothing and wash before reuse.		
6.1.2. Fo	or emergency responders			
Protective e	equipment	: Equip cleanup crew with proper protection.		
6.2. En	vironmental precautions			

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage. Contain leaking substance, pump over in suitable containers.
Methods for cleaning up	Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Small quantities of liquid spill: take up in non- combustible absorbent material and shovel into container for disposal. Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage			
7.1. Precautions	r safe handling		
Precautions for safe han	ng : meet the legal requirements. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin. Presents no particular risk when handled in accordance with good occupational hygiene practice. Provide good ventilation in process area to prevent formation of vapour.		
Hygiene measures	: Use good personal hygiene practices. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.		
7.2. Conditions f	safe storage, including any incompatibilities		
Technical measures	: Take precautionary measures against static discharge.		
Storage conditions	 Meet the legal requirements. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Store in a well-ventilated place. 		
Storage temperature	: < 45 °C		
Storage area	: Meet the legal requirements. Protect from heat and direct sunlight. Keep container tightly closed in a cool, well-ventilated place. Ventilation along the floor.		
Special rules on packagi	: Keep only in original container. correctly labelled.		
7.3. Specific end	se(s)		

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

-	-	-	-	-
Italy -	Portugal - USA	ACG	IH TWA (ppm)	
ACGIH				

100 ppm

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

2-ethylhexan-1-ol (104-76-7)			
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	110 mg/m³	
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm	
2-butoxyethanol (111-7	76-2)		
EU	IOELV TWA (mg/m³)	98 mg/m³	
EU	IOELV TWA (ppm)	20 ppm	
EU	IOELV STEL (mg/m ³)	246 mg/m³	
EU	IOELV STEL (ppm)	50 ppm	
Belgium	Limit value (mg/m³)	98 mg/m³	
Belgium	Limit value (ppm)	20 ppm	
Belgium	Short time value (mg/m ³)	246 mg/m ³	
Belgium	Short time value (ppm)	50 ppm	
Belgium	Remark (BE)	D	
Netherlands	Grenswaarde TGG 8H (mg/m ³)	100 mg/m³	
Netherlands	Grenswaarde TGG 8H (ppm)	20 ppm	
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	246 mg/m³	
Netherlands	Grenswaarde TGG 15MIN (ppm)	50 ppm	
xylene (1330-20-7)			
EU	IOELV TWA (mg/m³)	221 mg/m³	
EU	IOELV TWA (ppm)	50 ppm	
EU	IOELV STEL (mg/m ³)	442 mg/m³	
EU	IOELV STEL (ppm)	100 ppm	
Belgium	Limit value (mg/m³)	221 mg/m³	
Belgium	Limit value (ppm)	50 ppm	
Belgium	Short time value (mg/m ³)	442 mg/m ³	
Belgium	Short time value (ppm)	100 ppm	
Belgium	Remark (BE)	D	
United Kingdom	WEL STEL (ppm)	100 ppm	

8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide good ventilation in process area to prevent formation of vapour. Does not require any specific or particular technical measures.

Personal protective equipment

Hand protection

Other information

: Gloves. Safety glasses.



- : Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.
- : Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

9.1. Information on basic	physical and chemical properties
Physical state	: Liquid
Appearance	: Clear.
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	:
Relative evaporation rate (butylacetate=1)	: No data available
refraction index	: 1,44
Melting point	: No data available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

Freezing point	: No data available
Boiling point	: No data available
Flash point	: 40 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density @20°C	: 833 kg/m³
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: 1,8 mm²/s
Viscosity, dynamic @40°C	: No data available
Viscosity	:
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content Additional information : 90,46 %

: The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions. Heating may cause a fire.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours. Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information		
11.1. Information on toxi	cological effects	
Acute toxicity	: Harmful: may cause lung damage if swallowed	
Catalytic Converter & Oxyge	n Sensor Cleaner	
ATE CLP (dermal)	1100,000 mg/kg bodyweight	
ATE CLP (dust,mist)	4,167 mg/l/4h	
2-ethylhexan-1-ol (104-76-7	')	
ATE CLP (dust,mist)	1,500 mg/l/4h	
2-butoxyethanol (111-76-2)		
ATE CLP (oral)	500,000 mg/kg bodyweight	
ATE CLP (dermal)	1100,000 mg/kg bodyweight	
ATE CLP (dust,mist)	1,500 mg/l/4h	
xylene (1330-20-7)		
ATE CLP (dermal)	1100,000 mg/kg bodyweight	
00/00/0045		0/40

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

xylene (1330-20-7)	
ATE CLP (dust,mist)	1,500 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Causes damage to organs (central nervous system) through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
SECTION 12: Ecological inform	nation
12.1. Toxicity	
Ecology - general	: This product contains hazardous components for the aquatic environment. May cause long lasting harmful effects to aquatic life.
Ecology - water	: Harmful to aquatic life with long lasting effects.
12.2. Persistence and degradab	ility

2-ethvlhexan-1-ol (104-76-7)

2-etilyinexan-1-01 (104-70-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
xylene (1330-20-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photolysis in the air.
12.3. Bioaccumulative potential	
2-ethylhexan-1-ol (104-76-7)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
xylene (1330-20-7)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
12.4. Mobility in soil	
xylene (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

12.5. Results of PBT and vPvB assessment

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

13.1. Waste treatment methods	
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Remove to an authorized waste treatment plant. Avoid release to the environment.
European List of Waste (LoW) code	: 18 01 06* - chemicals consisting of or containing dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 1993
--------------	--------

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

14.2. UN proper shipping name	
Proper Shipping Name (ADR)	: FLAMMABLE LIQUID, N.O.S.
Transport document description (ADR)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (xylene, di-tert-butylperoxide), 3, III, (D/E)
14.3. Transport hazard class(es)	
Class (ADR)	: 3
Danger labels (ADR)	: 3
14.4. Packing group	
Packing group (ADR)	: III
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for use	er
14.6.1. Overland transport	
Hazard identification number (Kemler No.)	: 30
Classification code (ADR)	: F1
Orange plates	30 1993
Special provisions (ADR)	: 274, 601, 640E
Transport category (ADR)	: 3
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	: 51
Excepted quantities (ADR)	: E1
EAC code	: •3YE
14.6.2. Transport by sea	
EmS-No. (1)	: F-E, S-E
14.6.3. Air transport	
Instruction "cargo" (ICAO)	: 366
Instruction "passenger" (ICAO)	: 355
Instruction "passenger" - Limited quantities (ICAO)	: Y344

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances VOC content : 90,46 %

15.1.2. National regulations

Water hazard class (WGK)

: 2 - hazard to waters

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of R-, H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard,
	Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Lig. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Org. Perox. E	Organic Peroxides, Type E
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure,
	Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H242	Heating may cause a fire
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H372	Causes damage to organs through prolonged or repeated
	exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
R10	Flammable
R11	Highly flammable
R20	Harmful by inhalation
R20/21	Harmful by inhalation and in contact with skin
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed
R36/37/38	Irritating to eyes, respiratory system and skin
R36/38	Irritating to eyes and skin
R38	Irritating to skin
R48/20	Harmful: danger of serious damage to health by prolonged
	exposure through inhalation
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R68	Possible risk of irreversible effects
R7	May cause fire
F	Highly flammable
Ν	Dangerous for the environment
0	Oxidising
Xi	Irritant
Xn	Harmful

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) No. 2015/830

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product