# LPS

# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

n

of the mixture

Registration number

Synonyms None.

Part Number M01422, M01428, M01405, M01455

Issue date 22-March-2016

Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

LPS® PreSolve

Identified uses A solvent degreasing agent designed for removing tar, adhesives, grease, oil and other residues

from metal and other hard surfaces.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

**Supplier** Alsco Ltd

Company name Unit 13 Hillmead Industrial Estate

Address Marshall Road

Swindon, Wiltshire

United Kingdom SN5 5FZ

**Telephone** +44 1793 733 900 **In Case of Emergency** +001 703-527-3887

Manufacturer

Company name ITW Pro Brands

Address 4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)

Website http://www.lpslabs.com
e-mail lpssds@itwprobrands.com

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Directive 67/548/EEC or 1999/45/EC as amended

**Classification** R10, Xn;R65, Xi;R36/38, R43, N;R51/53

The full text for all R-phrases is displayed in section 16.

#### Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 3 H226 - Flammable liquid and

vapour.

**Health hazards** 

exposure

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.
Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Skin sensitisation Category 1 H317 - May cause an allergic skin

reaction.

reaction

Category 1

Category 3 narcotic effects

H336 - May cause drowsiness or

dizziness.

H304 - May be fatal if swallowed and enters airways.

**Environmental hazards** 

long-term aquatic hazard

Aspiration hazard

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with

long lasting effects.

Specific target organ toxicity - single

**Hazard summary** 

Physical hazards Flammable.

Health hazards Irritating to eyes and skin. May cause sensitisation by skin contact. Harmful: may cause lung

damage if swallowed. Occupational exposure to the substance or mixture may cause adverse

health effects.

**Environmental hazards** 

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Specific hazards

Flammable. Harmful if swallowed. Irritating to eyes and skin. May cause sensitisation by skin contact. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Main symptoms Irritating to eyes and skin. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. May cause sensitisation by skin contact. Symptoms may include redness, oedema, drying,

defatting and cracking of the skin. Dermatitis. Rash.

#### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Distillates Petroleum Hydrotreated Light, d-limonene

Hazard pictograms



Signal word Danger

**Hazard statements** 

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

#### Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed. P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapour.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection/face protection.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see this label).

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use appropriate media to extinguish.

P391 Collect spillage.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information Not applicable. 2.3. Other hazards None known.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

**General information** 

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Distillates Petroleum Hydrotreated Light		ed 60 - 70	64742-47-8 265-149-8	-	649-422-00-2	
Classification:	DSD:	Xn;R65				
	CLP:	Flam. Liq. 3;H2	226, Asp. Tox. 1;H30	04, Skin Irrit. 2;H315, STOT SE	3;H336	
3-Methoxy-3-methyl-1-	butanol (N	/IMB) 10 - 20	56539-66-3 260-252-4	-	-	
Classification:	DSD:	Xi;R36				
	CLP:	Eye Irrit. 2;H31	9			
d-limonene		10 - 20	5989-27-5 227-813-5	-	601-029-00-7	
Classification:	DSD:	R10, Xn;R65, X	Ki;R38, R43, N;R50/	53		С
	CLP:	Flam. Liq. 3;H2	226, Asp. Tox. 1;H30	04, Skin Irrit. 2;H315, Skin Sen	s. 1;H317,	С

#### List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008. DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance. PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Aquatic Acute 1;H400, Aquatic Chronic 1;H410

Composition comments The full text for all R- and H-phrases is displayed in section 16.

#### **SECTION 4: First aid measures**

In the case of accident or if you feel unwell, seek medical advice immediately (show the label **General information** 

where possible). Ensure that medical personnel are aware of the material(s) involved, and take

precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Get medical attention if irritation develops and

persists.

Eye contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses.

Get medical attention if irritation develops and persists.

Call a physician or poison control centre immediately. Only induce vomiting at the instruction of Ingestion

medical personnel. Never give anything by mouth to an unconsious person. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Rash. Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and

are reversible if exposure is stopped.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.

# **SECTION 5: Firefighting measures**

General fire hazards Flammable liquid and vapour. 5.1. Extinguishing media

Suitable extinguishing

media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

By heating and fire, harmful vapours/gases may be formed. Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back.

5.3. Advice for firefighters

Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Avoid inhalation of vapours or mists. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the

6.2. Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapours or divert vapour cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

Use personal protection recommended in Section 8 of the SDS. For waste disposal, see section 13.

# **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapour. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

**7.3. Specific end use(s)** Not available.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Occupational exposure limits

Czech Republic. OELs. Government Components	Туре	Value	
3-Methoxy-3-methyl-1-butan ol (MMB) (CAS 56539-66-3)	Ceiling	200 mg/m3	
· () (	TWA	100 mg/m3	

Finland. Workplace Exposu Components	Туре	Value			
d-limonene (CAS	STEL	280 mg/m3			
5989-27-5)	TWA	50 ppm 140 mg/m3 25 ppm			
	lvisory OELs). Commission for the Inv	estigation of Health Hazard	ds of Chemical Compound		
in the Work Area (DFG) Components	Туре	Value	Form		
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	140 mg/m3	Vapor and aerosol.		
d-limonene (CAS 5989-27-5)	TWA	20 ppm 28 mg/m3	Vapor and aerosol.		
,		5 ppm			
Germany. TRGS 900, Limit \ Components	/alues in the Ambient Air at the Workp Type	lace Value			
d-limonene (CAS	AGW	28 mg/m3			
5989-27-5)		5 ppm			
Norway. Administrative Nor Components	ms for Contaminants in the Workplace Type	Value			
d-limonene (CAS	TLV	140 mg/m3			
5989-27-5)		25 ppm			
Switzerland. SUVA Grenzwe		Value			
Components	Туре				
d-limonene (CAS 5989-27-5)	STEL	80 mg/m3			
	TWA	14 ppm 40 mg/m3 7 ppm			
ogical limit values	No biological exposure limits noted for	the ingredient(s).			
ommended monitoring cedures	Follow standard monitoring procedures.				
ived no-effect level (DNEL)	Not available.				
dicted no effect centrations (PNECs)	Not available.				
Exposure controls					
ropriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level.				
vidual protection measures,	such as personal protective equipment	nt			
General information	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Use personal protective equipment as required.				
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.				
Skin protection					
- Hand protection	Chemical resistant gloves are recomme	ended.			
- Other	Wear suitable protective clothing.				
	No personal respiratory protective equipment normally required. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are no				

air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate

Thermal hazards

protection.

Not applicable.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

**Environmental exposure** 

controls

Contain spills and prevent releases and observe national regulations on emissions. Environmental

manager must be informed of all major releases.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical state Liquid. Form Liquid.

Colour Clear, Off-white.

**Odour** Orange

Odour threshold

pH

Not applicable

Melting point/freezing point

Initial boiling point and boiling

Not established

> 150 °C (> 302 °F)

range

Flash point 40,0 °C (104,0 °F) Tag closed cup

Evaporation rate > 0,1 BuAc
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

0,7 %

(%)

Flammability limit - upper 6 %

(%)

Vapour pressure < 5 mm Hg @ 20°C

Vapour density > 1 (Air = 1)

Relative density Not available.

Solubility(ies)

Solubility (water) < 15 %

Solubility (other) Not available.

Partition coefficient Not established

(n-octanol/water)

Auto-ignition temperature> 200 °C (> 392 °F)Decomposition temperatureNot establishedViscosity< 3 cSt @ 25°C</th>Explosive propertiesNot available.Oxidising propertiesNot available.

9.2. Other information

 $\begin{array}{ll} \mbox{Heat of combustion} & > 30 \mbox{ kJ/g} \\ \mbox{Percent volatile} & 100 \mbox{ \%} \\ \end{array}$ 

Specific gravity 0,82 - 0,86 @ 20°C

VOC (Weight %) 100 % per U.S State and Federal Consumer Product Regulations.

# **SECTION 10: Stability and reactivity**

**10.1. Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions. Risk of ignition.10.3. Possibility of hazardous No dangerous reaction known under conditions of normal use.

**10.4. Conditions to avoid** Heat, flames and sparks. Avoid temperatures exceeding the flash point.

**10.5. Incompatible materials** Strong oxidising agents.

**10.6. Hazardous** Carbon oxides.

decomposition products

reactions

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

**Inhalation** May cause drowsiness and dizziness.

Skin contact Causes skin irritation. May cause sensitisation by skin contact.

**Eye contact** Causes eye irritation.

**Ingestion** Harmful if swallowed. May be fatal if swallowed and enters airways.

**Symptoms** Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Defatting of the skin. Vapours have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting

11.1. Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test results

3-Methoxy-3-methyl-1-butanol (MMB) (CAS 56539-66-3)

Acute Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Oral

LD50 Mouse 5830 mg/kg

Rat > 2000 mg/kg

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

> 2000 mg/kg, 24 Hours

Inhalation

Aerosol

LC50 Cat > 6.4 mg/l, 6 Hours

Rat > 7,5 mg/l, 6 Hours > 4,3 mg/l, 4 Hours

Vapour

LC50 Rat > 0,1 mg/l, 8 Hours

Oral

LD50 Rat > 5000 mg/kg

d-limonene (CAS 5989-27-5)

**Acute** 

Oral

LD50 Mouse 5600 - 6600 mg/kg

Rat > 2000 mg/kg

**Skin corrosion/irritation**Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

**Respiratory sensitisation** Not a respiratory sensitizer.

**Skin sensitisation** May cause sensitisation by skin contact.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

d-limonene (CAS 5989-27-5)

3 Not classifiable as to carcinogenicity to humans.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Narcotic effects.

Specific target organ toxicity - N

repeated exposure

Not classified.

Aspiration hazard May be harmful if swallowed and enters airways. If aspirated into lungs during swallowing or

vomiting, may cause chemical pneumonia, pulmonary injury or death.

Mixture versus substance

information

Not available.

Not available. Other information

# **SECTION 12: Ecological information**

12.1. Toxicity Toxic to aquatic life with long lasting effects.

Components **Species Test results** 

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout

(Oncorhynchus mykiss)

d-limonene (CAS 5989-27-5)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 69,6 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 0,619 - 0,796 mg/l, 96 hours

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative potential No data available.

Partition coefficient n-octanol/water (log Kow)

d-limonene 4.232

**Bioconcentration factor (BCF)** Not available.

12.4. Mobility in soil Readily absorbed into soil.

12.5. Results of PBT

Not available.

and vPvB assessment

12.6. Other adverse effects None known.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

2,9 mg/l, 96 hours

emptied.

**EU** waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material Disposal methods/information

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### **SECTION 14: Transport information**

# **ADR**

14.1. UN number UN1993

14.2. UN proper shipping FLAMMABLE LIQUID, N.O.S. (d-limonene, Naptha)

name

for user

14.3. Transport hazard class(es)

Class 3 Subsidiary risk Label(s) 3 30 Hazard No. (ADR) Tunnel restriction code D/E 14.4. Packing group Ш 14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

**RID** 

UN1993 14.1. UN number

14.2. UN proper shipping FLAMMABLE LIQUID, N.O.S. (d-limonene, Naptha)

name

14.3. Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No.

Read safety instructions, SDS and emergency procedures before handling. Read safety 14.6. Special precautions

instructions, SDS and emergency procedures before handling. for user

**ADN** 

14.1. UN number UN1993

14.2. UN proper shipping Flammable Liquid (d-limonene, Naptha)

name

14.3. Transport hazard class(es)

Class 3 Subsidiary risk Label(s) 3 Ш 14.4. Packing group 14.5. Environmental hazards No.

Read safety instructions, SDS and emergency procedures before handling. Read safety 14.6. Special precautions for user

instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number

14.2. UN proper shipping Flammable liquid, n.o.s. (d-limonene, Naptha)

name

14.3. Transport hazard class(es)

3 Class Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards Yes 3L **ERG Code** 

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN1993 14.1. UN number

FLAMMABLE LIQUID, N.O.S. (d-limonene, Naptha), MARINE POLLUTANT 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Class 3 Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards Marine pollutant Yes

F-E, S-E **EmS** 

Read safety instructions, SDS and emergency procedures before handling. Read safety 14.6. Special precautions for user

instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk Not available.

according to Annex II of Marpol

and the IBC Code

M01422, M01428, M01405, M01455 Version #: 01 Issue date: 22-March-2016

#### ADN; ADR; IATA; IMDG; RID



#### Marine pollutant



**General information** 

IMDG Regulated Marine Pollutant.

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

#### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Not listed.

# Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances

d-limonene (CAS 5989-27-5)

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended

Distillates Petroleum Hydrotreated Light (CAS 64742-47-8) d-limonene (CAS 5989-27-5)

## Directive 94/33/EC on the protection of young people at work, as amended

d-limonene (CAS 5989-27-5)

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws.

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work. Follow national regulation for work

with chemical agents.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data. if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 Harmful: may cause lung damage if swallowed.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**Revision information** Product and Company Identification: Product and Company Identification

SECTION 2: Hazards identification: Prevention SECTION 2: Hazards identification: Storage

SECTION 3: Composition/information on ingredients: Component information

SECTION 5: Firefighting measures: Unsuitable extinguishing media SECTION 6: Accidental release measures: For non-emergency personnel SECTION 6: Accidental release measures: 6,2. Environmental precautions

SECTION 7: Handling and storage: 7,2. Conditions for safe storage, including any incompatibilities

SECTION 8: Exposure controls/personal protection: - Other

SECTION 11: Toxicological information: Inhalation Transport Information: Material Transportation Information

GHS: Classification

**Training information** 

**nformation** Follow training instructions when handling this material.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

 $\label{eq:material name: LPS} \textbf{Material name: LPS} \textbf{@ PreSolve - ITW Pro Brands (EU)}$ 

M01422, M01428, M01405, M01455 Version #: 01 Issue date: 22-March-2016