

ULTRAFORM 2030

Page: 1

Compilation date: 09/12/2014

Revision date: 05/02/2016

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ULTRAFORM 2030

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Metal forming fluid

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

	ROCOL House
	Swillington
	Leeds
	West Yorkshire
	LS26 8BS
	ENGLAND
Tel:	+44 (0) 113 232 2700
Fax:	+44 (0) 113 232 2740

Email: <u>customer-service@rocol.com</u>

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Lact.: H362; -: EUH066
Most important adverse effects:	Repeated exposure may cause skin dryness or cracking. Causes serious eye irritation.
	May cause harm to breast-fed children. Very toxic to aquatic life. Very toxic to aquatic life
	with long lasting effects.

2.2. Label elements

Label elements:	
Hazard statements:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H319: Causes serious eye irritation.
	H362: May cause harm to breast-fed children.
	H400: Very toxic to aquatic life.
	H410: Very toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS07: Exclamation mark
	GHS09: Environmental

ULTRAFORM 2030

Page: 2



Signal words:WarningPrecautionary statements:P260: Do not breathe dust/fumes/gas/mist/vapours/spray.P263: Avoid contact during pregnancy.P264: Wash thoroughly after handling.P273: Avoid release to the environment.P270: Do not eat, drink or smoke when using this product.P280: Wear protective gloves/protective clothing/eye protection/face protection.P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Removecontact lenses, if present and easy to do. Continue rinsing.P308+313: IF exposed or concerned: Get medical advice/attention.P337+313: If eye irritation persists: Get medical advice/attention.P391: Collect spillage.P501: Dispose of contents/container to local/national regulations.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

MINERAL OIL (NOTE L <3% DMSO EXTRACTABLE COMPONENTS)

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-155-0	64742-52-5	Substance with a Community workplace exposure limit.	-	30-50%
C14-C17 CHL	ORINATED PAR	AFFIN - REACH registered number(s): 01-2119519269-33-XXXX	
287-477-0	85535-85-9	-	Lact.: H362; Aquatic Chronic 1: H410; Aquatic Acute 1: H400; -: EUH066	30-50%
FATTY ACID	ALKANOLAMIDE	·		
202-281-7	93-83-4	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-10%

SODIUM SULPHONATE (IN MINERAL OIL)

	271-781-5	68608-26-4	-	Eye Irrit. 2: H319	1-10%
--	-----------	------------	---	--------------------	-------

ULTRAFORM 2030

Page: 3

MINERAL OIL (NOTE L - LESS THAN 3% DMSO EXTRACT)

265-090-8		Substance with a Community workplace exposure limit.	-	1-10%	

ALCOHOLS C16-C18, C18-UNSATURATED, ETHOXYLATED (<2,5 EO)

500-236-9	68920-66-1	-	Skin Irrit. 2: H315; Aquatic Chronic 3:	<1%
			H412	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

ULTRAFORM 2030

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

MINERAL OIL (NOTE L <3% DMSO EXTRACTABLE COMPONENTS)

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5mg/m3	10mg/m3	-	-

SODIUM SULPHONATE (IN MINERAL OIL)

UK 5 mg/m-3 10 mg/m-3

ULTRAFORM 2030

Page: 5

MINERAL OIL (NOTE L - LESS THAN 3% DMSO EXTRACT)

UK	5mg/m3	10mg/m3	-	-

DNEL/PNEC Values

Hazardous ingredients:

C14-C17 CHLORINATED PARAFFIN

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	6.7	Workers	-
DNEL	Dermal (repeated dose)	47.9	Workers	-
DNEL	Oral	0.58	Consumers	-
DNEL	Dermal	28.75	Consumers	-
DNEL	Inhalation	2.0	Consumers	-
PNEC	Fresh water	0.001	-	-
PNEC	Marine water	0.2	-	-
PNEC	Microorganisms in sewage treatment	80	-	-
PNEC	Fresh water sediments	5	-	-
PNEC	Marine sediments	1	-	-
PNEC	Soil (agricultural)	10.5	-	-

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area. The floor of the storage room must be
impermeable to prevent the escape of liquids.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Protective gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Brown		
Odour:	Characteristic odour		
Evaporation rate:	Negligible		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Miscible		
Viscosity:	Viscous		
Boiling point/range°C:	100	Flash point°C:	> 100
Autoflammability°C:	> 200	Relative density:	>1

ULTRAFORM 2030

Page: 6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

MINERAL OIL (NOTE L <3% DMSO EXTRACTABLE COMPONENTS)

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

C14-C17 CHLORINATED PARAFFIN

ORAL RAI LD50 > 2000 mg/kg

FATTY ACID ALKANOLAMIDE

DERMAL	RBT	LD50	> 2000	mg/kg
ORAL	RAT	LD50	> 2000	mg/kg

ALCOHOLS C16-C18, C18-UNSATURATED, ETHOXYLATED (<2,5 EO)

|--|

ULTRAFORM 2030

Page: 7

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

C14-C17 CHLORINATED PARAFFIN

ALGAE	96H ErC50	>3.2	mg/l
Daphnia magna	48H EC50	0.006	mg/l
FISH	96H LC50	>5000	mg/l

ALCOHOLS C16-C18, C18-UNSATURATED, ETHOXYLATED (<2,5 EO)

FISH 96H LC50	10 - 100	mg/l	
---------------	----------	------	--

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

ULTRAFORM 2030

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(C14-C17 CHLORINATED PARAFFIN)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	Compiled in accordance with REACH.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H362: May cause harm to breast-fed children.
	H400: Very toxic to aquatic life.
	H410: Very toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive

ULTRAFORM 2030

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.