## **Technical Data**



### Performance you can trust

## ULTRAFORM™ ADVANTAGE

High Performance, Chlorine Free Cold Metal Forming Lubricant

ULTRAFORM™ ADVANTAGE is a high performance, chlorine-free lubricant designed for all cold metal pressing and drawing operations. ULTRAFORM™ ADVANTAGE is unique in that it gives unprecedented levels of performance and outstanding economy.

For the most difficult operations, the product should be used undiluted to give the highest levels of performance. Where economy is required, the wide dilution range of ULTRAFORM™ ADVANTAGE enables the product to be extended using either oil or water.

#### **Features**

- High performance giving minimal scrap.
- Wide dilution range giving economy.
- Chlorine-free.
- Easy to clean.
- · Suitable for all metals.

#### **Directions for Use**

ULTRAFORM™ ADVANTAGE may be applied by brush, drip or airless spray system. Where absolute freedom from discolouration is essential, it is recommended that compatibility trials are performed.

#### RECOMMENDED DILUTION:

For the severest draws, use ULTRAFORM™ ADVANTAGE neat. For less severe operations, the product may be diluted with oil or water in ratios up to 10 parts of oil or water to 1 part ULTRAFORM™ ADVANTAGE, depending upon the particular operation. Stir continuously when adding ULTRAFORM™ ADVANTAGE to oil or water until the desired ratio is obtained.

#### PREPARATION OF A PASTE:

When the method of application requires the use of a paste, this can be obtained by mixing ULTRAFORM<sup>TM</sup> ADVANTAGE with equal amounts of water. Stir continuously whilst adding the water until a paste is achieved.

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

### ROCOL A division of MW Ltd









OHSAS 18001

INVESTOR IN PEOPLE

# **Technical Data**



Performance you can trust

## **ULTRAFORM™ ADVANTAGE**

Appearance	Brown liquid
Odour	Mild
рН	8.6 at 10:1
Density at 20°C	0.97 g/cm <sup>3</sup>
Storage	Store at normal ambient temperature (5 to 30°C)
Pack Sizes – Part Codes	20 ltr - 86273
	200 ltr - 86279

Date: Jan-09

T +44 (0) 113 232 2600 **F** +44 (0) 113 232 2740

E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL ROCOL A division of // Ltd











