



SAFETY DATA SHEET
ULTRAGUARD SC

Page: 1

Compilation date: 09/06/2015

Revision date: 06/01/2016

Revision No: 9

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ULTRAGUARD SC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Coolant system cleaning fluid

1.3. Details of the supplier of the safety data sheet

Company name: Rocol

ROCOL House

Swillington

Leeds

West Yorkshire

LS26 8BS

ENGLAND

Tel: +44 (0) 113 232 2700

Fax: +44 (0) 113 232 2740

Email: customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314; Skin Sens. 1: H317

Most important adverse effects: Causes severe skin burns and eye damage. May cause an allergic skin reaction.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P260: Do not breathe vapours.

[cont...]

SAFETY DATA SHEET

ULTRAGUARD SC

Page: 2

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ALPHA,ALPHA',ALPHA"-TRIMETHYL-1,3,5-TRIAZINE-1,3,5(2H,4H,6H)-TRIETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
246-764-0	25254-50-6	-	Skin Sens. 1: H317; Acute Tox. 4: H302; Acute Tox. 4: H332; Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-10%

TRIDECYLPOLYETHYLENGLYCOL ETHER

-	69011-36-5	-	Eye Dam. 1: H318; Aquatic Chronic 3: H412	1-10%
---	------------	---	---	-------

ALKYL POLYGLYCOL ETHER

-	61827-42-7	-	Acute Tox. 4: H302; Eye Dam. 1: H318	1-10%
---	------------	---	--------------------------------------	-------

SODIUM HYDROXIDE - REACH registered number(s): 01-2119457892-27

215-185-5	1310-73-2	-	Skin Corr. 1A: H314	1-10%
-----------	-----------	---	---------------------	-------

SODIUM PYRITHIONE

223-296-5	3811-73-2	-	Acute Tox. 4: H302+312+332; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Aquatic Acute 1: H400; -: EUH070	<1%
-----------	-----------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Severe burns may occur.

[cont...]

SAFETY DATA SHEET

ULTRAGUARD SC

Page: 3

Eye contact: Corneal burns may occur.

Ingestion: Nausea and stomach pain may occur.

Inhalation: There may be coughing and a sore throat.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Use water spray to cool containers. Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

ULTRAGUARD SC

Page: 4

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not normally required.

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow

Odour: Characteristic odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Non-viscous

Boiling point/range°C: 100

Flash point°C: > 100

Autoflammability°C: > 200

Relative density: 1.07

pH: 12

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

[cont...]

SAFETY DATA SHEET

ULTRAGUARD SC

Page: 5

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Severe burns may occur.

Eye contact: Corneal burns may occur.

Ingestion: Nausea and stomach pain may occur.

Inhalation: There may be coughing and a sore throat.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM PYRITHIONE

DAPHNIA	48H EC50	0.022	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	0.0066	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

[cont...]

SAFETY DATA SHEET

ULTRAGUARD SC

Page: 6

12.4. Mobility in soil

Mobility: Non-volatile. Absorbed only slowly into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1719

14.2. UN proper shipping name

Shipping name: CAUSTIC ALKALI LIQUID, N.O.S.
(Sodium Hydroxide)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

[cont...]

SAFETY DATA SHEET

ULTRAGUARD SC

Page: 7

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Compiled in accordance with REACH.

.....
Product label must specify:

CONTAINS SUBSTANCE(S):

Sodium hydroxide (CAS 1310-73-2)

alpha,alpha',alpha"-Trimethyl-1,3,5-triazine-1,3,5(2H,4H,6H)-triethanol (CAS 25254-50-6)

Use biocides safely. Always read the label and product information before use.
.....

Phrases used in s.2 and s.3: EUH070: Toxic by eye contact.

H302: Harmful if swallowed.

H302+312+332: Harmful if swallowed, in contact with skin or if inhaled.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H400: Very toxic to aquatic life.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

