



Technical Data Sheet

Indu-Tek Long-Life CS00 Grease

Heavy Duty, Superior Performance, High Temperature, Water Resistant
Calcium Sulphonate Complex Grease

Long-Life CS00 Grease is a superior quality multi-purpose grease, formulated to meet the requirement of the most extreme industrial applications and diverse temperatures.

Long-Life CS00 Grease is suitable for all types of Anti-Friction, Plain Bearings and Sliding Surfaces.

Features and Benefits: -

- Extreme Load Bearing Capacity >600kg's weld load
- Excellent Operating temp range -30°C - 180°C
- Completely water resistant – no loss of consistency even when saturated
- Excellent Anti-Oxidation & Anti-Corrosion properties
- Does not contain lead, or other metallic substrates harmful to the Environment or Human Health
- Long-Life application – extends relubrication periods

Directions for Use: -

Long-Life CS00 Grease can be applied by hand, or by a centralised lubrication system compatible for pumping an NLGI No.00 grease.

As with all greases used for the first-time check compatibility with the grease applied previously and if necessary purge the bearings prior to application.

Packaging: -

Long-Life CS00 Grease is available in 12.5kg 18kg, 50kg and 180kg drums.

Part Number: ML-11546

This data is supplied in good faith but without warranty. We do not assume responsibility and expressly disclaim any liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product. This Data Sheet was prepared solely for the product stated and should not be used for any other product.



A British Lubricant Company

Mako-Lube Lubricants is a registered
trademark & brand of Brit-Lube Limited

Brit-Lube Ltd, Manchester, UK. Tel: +44 (0)161 777 9970
www.mako-lube.com info@mako-lube.com



Specific Data

Indu-Tek Long-Life CS00 Grease

Heavy Duty, Superior Performance, High Temperature, Water Resistant
Calcium Sulphonate Complex Grease

Typical Characteristics and properties

Appearance	-	Smooth buttery grease
Colour	-	Brown
NLGI classification (IP50)	-	00
Worked penetration (IP50)	-	400 to 430
Base oil Viscosity	-	460 cst
Water wash out	-	< 1%
Dropping point	-	>280°C
Timken OK Load (IP236)	-	60 lbs
Thickener	-	Calcium sulphonate complex
Working temperature range	-	-30°C to 180°C short periods

This data is supplied in good faith but without warranty. We do not assume responsibility and expressly disclaim any liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product. This Data Sheet was prepared solely for the product stated and should not be used for any other product.



A British Lubricant Company

*Mako-Lube Lubricants is a registered
trademark & brand of Brit-Lube Limited*

Brit-Lube Ltd, Manchester, UK. Tel: +44 (0)161 777 9970
www.mako-lube.com info@mako-lube.com