

LPS[®] MICRO-X NU

FAST EVAPORATING CONTACT CLEANER

VOC COMPLIANT



FEATURES

- Reduced VOCs (Volatile Organic Compounds)
- Conforms to the VOC regulations of CARB (California Air Resources Board), OTC (Ozone Transport Commission) and LADCO (Lake Michigan Air Directors Consortium)
- Quick penetration
- Safe on plastics
- No residue
- Ideal for electronic and fine parts
- Does not contain any chlorinated solvents
- Removes dirt, dust, flux and other contaminants
- Inverta Spray Valve lets you spray in an upright or inverted position

APPLICATIONS

- Circuit Breakers
- Connectors
- Contacts
- Controls
- Fluid Systems
- Generators
- Instrumentation
- Keyboards
- Magnetic Tape Heads
- Motors
- Office Equipment
- Printed Circuits
- Relays
- Semiconductor Assemblies
- Sensors
- Switch Gears
- Switches
- Telecommunication Equipment
- Telephone Equipment
- Terminals
- TV Tuners



PACKAGE

Net Fill
11 oz. (312 grams) aerosol

Part No.
06616

PROPERTIES

Surface Tension:
17.3 dynes/cm @ 77°F (25°C)

KB Value:
24

Specific Gravity (H₂O=1):
0.64 – 0.66 @ 77°F (25°C)

Flash Point:
0°F (-18°C) TCC

VOC Content:
74%, 481 g/L, 4.01 lb./gal (aerosol)

% HCFCs:
None

Propellant:
HFC 134a

% Non-volatiles:
50 ppm maximum

Value Performance

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2009 LPS Laboratories • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2237 • Rev. 5/2009