

Performance you can trust

MOISTURE GUARD Clear Spray Indoor corrosion preventative

MOISTURE GUARD Clear Spray is a thin, almost dry corrosion preventative film suitable for the temporary indoor protection of components such as bearings, gears, pressings and any machined metal product which requires protection from corrosive attack - whether in storage, transit or between operations.

MOISTURE GUARD Clear Spray is ideal as a colourless, medium/long term indoor corrosion protection of bare metal components and mould tools particularly where condensation is a problem.

Features

- Effective indoor corrosion protection.
- Tenacious soft film - easily handled.
- Almost dry film - does not attract dirt and dust.
- Particularly effective in damp or humid environments.

Directions for Use

Shake well, hold upright and spray from a distance of approximately 15-30cm (6-12 inches). One pass usually provides sufficient protection. Ensure adequate ventilation. Do not spray onto naked flame or any incandescent material.

N.B. Test compatibility with painted or coated surfaces, plastics and rubbers if the product is liable to come into contact with these materials.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Performance you can trust

MOISTURE GUARD Clear Spray

Propellant	Hydrocarbon blend
Solvent	Non-chlorinated hydrocarbon
Colour	Clear
Film Type	Almost dry, soft flexible film
Film Thickness (Typical)	Approximately 3 to 5 microns
Curing Time	Touch dry within 15 to 30 minutes
Protection Period	Up to 5 years indoors. Short term outdoors
Storage	Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.
Pack Sizes – Part Codes	400ml - 69025

Date: June-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BSI
BS EN ISO 9001
Certificate No. FM 12448



BSI
BS EN ISO 14001
Certificate No. EMS 67596



BSI
OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.