



SAFETY DATA SHEET

SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Page: 1

Compilation date: 31/05/2015

Revision date: 06/01/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Product code: 42036 Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Achitectural repair compound

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House

Swillington

Leeds

West Yorkshire

LS26 8BS

ENGLAND

Tel: +44 (0) 113 232 2700

Fax: +44 (0) 113 232 2740

Email: customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -: EUH205

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. Contains epoxy constituents. May produce an allergic reaction.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

EUH205: Contains epoxy constituents. May produce an allergic reaction.

[cont...]

SAFETY DATA SHEET

SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Page: 2

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental



Signal words: Warning

Precautionary statements: P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see instructions on this label).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	50-70%

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL - REACH registered number(s): 01-2119454392-40

500-006-8	9003-36-5	-	Aquatic Chronic 2: H411; Skin Sens. 1: H317; Skin Irrit. 2: H315	10-30%
-----------	-----------	---	--	--------

OXIRANE, MONO[(C10-16-ALKYLOXY)METHYL] DERIVS.

268-358-2	68081-84-5	-	Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411; Skin Irrit. 2: H315	1-10%
-----------	------------	---	--	-------

TITANIUM DIOXIDE

-	13463-67-7	Substance with a Community workplace exposure limit.	-	1-10%
---	------------	--	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Any contaminated clothing must be

[cont...]

SAFETY DATA SHEET

SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Page: 3

thoroughly cleaned before re-using. Obtain medical attention if soreness or redness persists.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Wash out mouth with water. Keep patient at rest and obtain medical attention. Seek medical attention if you feel unwell.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Seek medical attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Dry chemical powder. Carbon dioxide. Alcohol resistant foam. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

[cont...]

SAFETY DATA SHEET

SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

TITANIUM DIOXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	4mg/m3	-

DNEL/PNEC Values

SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	10 mg/kg bw/d	Workers	Chronic Systemic
DNEL	Oral	700 mg/kg bw/d	Consumers	Chronic Systemic
PNEC	Fresh water	0.127	-	-
PNEC	Fresh water sediments	1000	-	-
PNEC	Marine water	1	-	-
PNEC	Marine sediments	100	-	-
PNEC	Food chain	1667	-	-
PNEC	Microorganisms in sewage treatment	100 mg/l	-	-
PNEC	Soil (agricultural)	100	-	-

Hazardous ingredients:

TITANIUM DIOXIDE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	10	Workers	Systemic

[cont...]

SAFETY DATA SHEET

SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Page: 5

PNEC	Fresh water	0.127	-	-
PNEC	Marine water	1	-	-
PNEC	Fresh water sediments	1000	-	-
PNEC	Soil (agricultural)	100	-	-
PNEC	Microorganisms in sewage treatment	100	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Grey

Odour: Barely perceptible odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Insoluble

Viscosity: No data available.

Boiling point/range°C: 200

Melting point/range°C: No data available.

Flammability limits %: lower: 10

upper: 20

Flash point°C: 100

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 1.20

pH: No data available.

VOC g/l: 0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET

SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Page: 6

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat.

10.5. Incompatible materials

Materials to avoid: Amines. Strong oxidising agents. Strong bases.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

OXIRANE, MONO[(C10-16-ALKYLOXY)METHYL] DERIVS.

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

TITANIUM DIOXIDE

DUST/MIST	RAT	4H LC50	>6.8	mg/l
ORAL	RAT	LD50	>5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

[cont...]

SAFETY DATA SHEET

SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Page: 7

Inhalation: Exposure may cause coughing or wheezing.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL

ALGAE	72H EC50	1.8	mg/l
ALGAE	72H IC50	1.8000	mg/l
DAPHNIA	48H EC50	1.6000	mg/l
FISH	96H LC50	0.5500	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes. The following data applies to the base component unreacted with the hardener part, as once reacted in the ratio supplied the harmful constituents will react to form inert product:
Hazardous for water. Do not allow the product to reach ground water, water bodies or sewage systems. Toxic to aquatic organisms. Danger to drinking water if even small quantities leak into soil.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

[cont...]

SAFETY DATA SHEET

SAFE STEP HEAVY DUTY EPOXY REPAIR COMPOUND - BASE

Page: 8

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT})

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Compiled in accordance with REACH.

Phrases used in s.2 and s.3: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

