

## WD Spray

### Multi-purpose penetrating, lubricating and water displacing spray

#### Product Overview

ROCOL® WD Spray is a multi-purpose maintenance product that penetrates, lubricates, displaces water and protects against corrosion.

It is ideal for use as a general lubricant to lubricate and protect small components such as hinges and locks.

The product is also particularly suitable for the protection and drying out of engine ignition systems, coils distributors, high tension (HT) leads and spark plugs.

#### Typical Applications

Small industrial equipment, engine ignition systems, hinges and locks, seized components.

#### Features and Benefits

- Excellent penetration.
- Efficient loosening of rust, scale, grease and general dirt and grime.
- Powerful jet application to mechanically penetrate rust and debris.
- Displaces water – ideal for drying out engine ignition systems.
- Fast acting formulation.
- Provides a light anti-corrosive film to protect components after application.

#### Directions for Storage and Use

- Shake aerosol well before use.
- Test compatibility with plastics and rubbers and painted or coated surfaces prior to application.
- Ensure electrical equipment is switched off and is electrically isolated.
- Hold can upright and apply from a distance of 15 – 30cm
- In severe cases, applying the product for a second time after several minutes may be beneficial to displace residual moisture or to free seized components.
- Use only in well ventilated areas and do not apply to very hot surfaces.
- Store below +50°C, out of direct sunlight.
- Shelf life is 2 years from date of manufacture.
- Consult safety data sheet before use.

#### Pack Sizes

Pack Size	Part Code
300ml	34271

## WD Spray

**Multi-purpose penetrating, lubricating and water displacing spray**

Property	Test Method	Result
Appearance	Visual	Amber liquid
Base Type	N/A	Mineral oil
Solvent	N/A	Hydrocarbon
Propellant	N/A	CO <sub>2</sub> (Carbon dioxide)
Odour	N/A	Characteristic
Density (kg/m <sup>-3</sup> )	RTM 3	0.87
Flash Point (°C)	PMCC	>75°C
Water Solubility	N/A	Insoluble

Values quoted above are typical and do not constitute a specification.

### Safety Data Sheets

Safety data sheets are available for download from our website [www.rocol.com](http://www.rocol.com) or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 1    Date: 01-11

T +44 (0) 113 232 2600

F +44 (0) 113 232 2740

E [customer-service@rocol.com](mailto:customer-service@rocol.com)

[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

**ROCOL** A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



**INVESTORS  
IN PEOPLE**